



Pressurized Eyewash

Self-Contained System

Self-contained, pressurized, portable 15-gallon eyewash with an ASME rated tank is an ideal solution for a facility's ANSI eyewash requirements in locations without access to a continuous potable water source and where an ASME tank is required.

- » 15 Gallons
- » Provides 15 minutes of flushing
- » Air pressure gauge
- » Pressure relief valve
- » Tire-type air fill valve
- » Certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment



Product Features:

- » Stainless steel constructed tank makes for a solid portable unit with added resistance against corrosion and breakage
- » Green polyethylene plastic dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation.
- » Valve comes equipped with stainless steel ball and stem for added protection against corrosion and breakage. Full continuous flow occurs with the simple push of a stainless steel flag.

Regulations in Compliance with:

- » ANSI Z358.1

Part Number:

- » EYEWASH-PRZ

Safety:

- » Air pressure gauge, pressure relief valve, and tire-type air fill valve decrease the possibility of mishaps and make for a safer piece of emergency equipment.
- » Green ABS plastic soft-flo anti-surge heads

Recommended Products:

- » Deluxe Sign Kit



- » Hydrogen Gas Monitor

